









Choose us, choose the future!













Supplier:	EVVA TECHNOLOGY CO., LIMITED
website:	www.evva-tech.com
Year of establishment:	2006
Address:	BldA3, New Material Industrial Park of Silicon Valley, Shenzhen 518110, China
Email:	info@evva-tech.com
Tel/Fax:	Tel: +86-755-8374 6079 Fax: +86-755-8374 6078

High-end Rechargeable Battery Cell Catalogue

Brand	Model	Nominal Voltage/Capacity	Photo	Full Charge Voltage	Continuous Discharge (Max.)	Quick Details	MOQ (pcs)	Availability
Sony	US18650VTC3	3.7V/1600mAh		4.2±0.05V	30A	1) Min. capacity: 1500mAh 2) Charge current: 1.5A 3) Max. charge current: 10A 4) Max. discharge current: 30A 5) Cut off voltage: 2.5V 6) Dimemsion: (D)18.35x (H) 65.1mm 7) weight: 45.1g (average)	100	YES
	 US18650VTC4	3.7V/2100mAh		4.2±0.05V	30A	1) Min. capacity: 2000mAh 2) Charge current: 2A 3) Max. discharge current: 30A 4) Peak discharge and time: 60A (75s) 5) Cut off voltage: 2.5V 6) Dimemsion: 18.20x65.1mm (max.) 7) weight: 48.0g (average)	100	YES
	 US18650VTC5	3.7V/2600mAh		4.2±0.05V	30A	1) Min. capacity: 2500mAh 2) Charge current: 2.5A 3) Charge time: 2.5h 4) Max. discharge current: 30A 5) Cut off voltage: 2.5V 6) Dimemsion: 18.35x65.2mm (max.) 7) weight: 44.3g (average)	100	YES
Panasonic	NCR18500	3.6V/2000mAh		4.2±0.03V	3.8A	1) Min. capacity: 1900mAh 2) Std. charge current: 1.33A 3) Charge time: 3h 4) Cut off voltage: 2.5V 5) Dimemsion: 18.5x49.5mm (max.) 6) weight: 35g (max.)	200	YES
	 NCR18650PF	3.6V/2900mAh		4.2±0.03V	10A	1) Min. capacity: 2750mAh 2) Std. charge current: 1.35A 3) Charge time: 4h 4) Max. discharge current: 10A 5) Cut off voltage: 2.5V 6) Dimemsion: 18.5x65.3mm (max.) 7) weight: 47g (max.)	100	YES
	NCR18650A	3.6V/3100mAh		4.2±0.05V	3.54A	1) Min. capacity: 2950mAh 2) Std. charge current: 0.6A 3) Charge time: 5h 4) Cut off voltage: 2.5V 5) Dimemsion: 18.5x65.3mm (max.) 6) weight: 48g (max.)	100	YES
	 NCR18650B	3.6V/3400mAh		4.2±0.03V	4.87A	1) Min. capacity: 3250mAh 2) Std. charge current: 1.625A 3) Charge time: 4h 4) Cut off voltage: 2.5V 5) Dimemsion: 18.5x65.1mm (max.) 6) weight: 48.5g (max.)	100	YES
	 NCR18650G	3.6V/3600mAh		4.2±0.05V	4.87A	1) Min. capacity: 3450mAh 2) Std. charge current: 1.08A 3) Charge time: 5h 4) Cut off voltage: 2.5V 5) Dimemsion: 18.5x65.3mm (max.) 6) weight: 48g (max.)	100	NO
	UR14430P	3.7V/660mAh		4.2±0.05V	1.32A	1) Min. capacity: 660mAh 2) Std. charge current: 0.66A 3) Charge time: 2.5h 4) Cut off voltage: 2.5V 5) Dimemsion: 42.9x13.9mm (max.) 6) weight: 17.5g (max.)	100	YES
	UR14500P	3.7V/840mAh		4.2±0.05V	1.68A	1) Min. capacity: 800mAh 2) Std. charge current: 0.8A 3) Charge time: 2.5h 4) Cut off voltage: 2.5V 5) Dimemsion: 13.9x45.2mm (max.) 6) weight: 20g (max.)	100	YES
	UR18500FK	3.7V/1700mAh		4.2±0.05V	3.24A	1) Min. capacity: 1620mAh 2) Std. charge current: 1.1A 3) Charge time: 3h 4) Cut off voltage: 3V 5) Dimemsion: 18.3x49.5mm (max.) 6) weight: 35g (max.)	100	YES
	UR16650ZTA	3.7V/2500mAh		4.35±0.05V	5A	1) Min. capacity: 2450mAh 2) Std. charge current: 1.45A 3) Charge time: 3h 4) Cut off voltage: 3.0V 5) Dimemsion: 16.39x64.9mm (max.) 6) weight: 41g (max.)	100	YES

Sanyo	 UR18650ZY	3.7V/2600mAh		4.2±0.05V	5A	1) Min. capacity: 2500mAh 2) Std. charge current: 1.75A 3) Charge time: 3h 4) Cut off voltage: 2.5V 5) Dimemision: 18.6x65.0mm (max.) 6) weight: 48g (max.)	100	YES
	 NCR18650BF	3.6V/3400mAh		4.2±0.03V	4.87A	1) Min. capacity: 3250mAh 2) Std. charge current: 1.625A 3) Charge time: 3.5h 4) Cut off voltage: 2.5V 5) Dimemision: 18.2x65.0mm (max.) 6) weight: 46.5g (max.)	100	YES
	 NCR18650BL	3.6V/3400mAh		4.2±0.03V	7A	1) Min. capacity: 3250mAh 2) Std. charge current: 1.62A 3) Charge time: 4h 4) Cut off voltage: 2.5V 5) Dimemision: 18.3x65.1mm (max.) 6) weight: 49g (max.)	100	YES
	 NCR18650GA	3.6V/3500mAh		4.2±0.03V	10A	1) Min. capacity: 3350mAh 2) Std. charge current: 1.475A 3) Charge time: 4.5h 4) Cut off voltage: 2.5V 5) Dimemision: 18.5x65.3mm (max.) 6) weight: 48g (max.)	100	YES
	UF103450P	3.7V/1880mAh		4.2±0.03V	3.76A	1) Min. capacity: 3350mAh 2) Std. charge current: 1.88A 3) Charge time: 3.0h 4) Cut off voltage: 2.75V 5) Dimemision: 18.5x65.3mm (max.) 6) weight: 40g (max.)	100	YES
Samsung SDI	INR18650-20R	3.6V/2000mAh		4.2±0.05V	22A	1) Min. capacity: 2000mAh 2) Charge current: 1A (3h) 3) Max. charge current: 4A (50min) 4) Max. discharge current: 22A 5) Cut off voltage: 2.5V 6) Dimemision: (D)18.4x (H) 65.0mm 7) weight: 45g (max.)	100	YES
	ICR18650-22F	3.6V/2200mAh		4.2±0.05V	4.4A	1) Min. capacity: 2150mAh 2) Charge current: 1.1A (3h) 3) Max. charge current: 2.2A (2.5h) 4) Max. discharge current: 4.4A 5) Cut off voltage: 2.75V 6) Dimemision: (D)18.4x (H) 65.0mm 7) weight: 44.5g (max.)	100	YES
	ICR18650-22P	3.62V/2150mAh		4.2±0.05V	10A	1) Min. capacity: 2050mAh 2) Charge current: 1.075A (3h) 3) Max. charge current: 2.15A (2.5h) 4) Max. discharge current: 10A 5) Cut off voltage: 2.75V 6) Dimemision: (D)18.4x (H) 65.0mm 7) weight: 44.5g (max.)	100	YES
	 INR18650-25R	3.6V/2500mAh		4.2±0.05V	20A	1) Min. capacity: 2500mAh 2) Charge current: 1.25A (3h) 3) Max. charge current: 2.5A (1h) 4) Max. discharge current: 20A 5) Cut off voltage: 2.5V 6) Dimemision: (D)18.4x (H) 65.0mm 7) weight: 45g (max.)	100	YES
	ICR18650-26F	3.7V/2600mAh		4.2±0.05V	5.2A	1) Min. capacity: 2550mAh 2) Charge current: 1.3A (3h) 3) Max. charge current: 2.6A (2.5h) 4) Max. discharge current: 5.2A 5) Cut off voltage: 2.75V 6) Dimemision: (D)18.4x (H) 65.0mm 7) weight: 47g (max.)	100	YES
	ICR18650-28A	3.75V/2800mAh		4.3±0.03V	5.6A	1) Min. capacity: 2700mAh 2) Charge current: 1.4A (3h) 3) Max. charge current: 2.8A (2.5h) 4) Max. discharge current: 5.6A 5) Cut off voltage: 2.75V 6) Dimemision: (D)18.4x (H) 65.0mm 7) weight: 48g (max.)	100	YES
	INR18650-29E	3.65V/2900mAh		4.2±0.05V	10A	1) Min. capacity: 2750mAh 2) Charge current: 1.375A (3h) 3) Max. charge current: 2.75A (2.5h) 4) Max. discharge current: 10A 5) Cut off voltage: 2.5V 6) Dimemision: (D)18.4x (H) 65.0mm 7) weight: 45g (max.)	100	YES
	 INR18650-30Q	3.6V/3000mAh		4.2±0.05V	15A	1) Min. capacity: 3000mAh 2) Charge current: 1.5A (3h) 3) Max. charge current: 4A (70min) 4) Max. discharge current: 15A 5) Cut off voltage: 2.5V 6) Dimemision: (D)18.4x (H) 65.0mm 7) weight: 48g (max.)	100	YES
	ICR18650-32A	3.75V/3200mAh		4.35±0.05V	6.4A	1) Min. capacity: 3100mAh 2) Charge current: 1.6A (3h) 3) Max. charge current: 3.2A 4) Max. discharge current: 6.4A 5) Cut off voltage: 2.75V 6) Dimemision: (D)18.4x (H) 65.0mm 7) weight: 50g (max.)	100	YES

LG Chem	18650 HB6	3.65V/1500mAh		4.25V	30A	1) Min. capacity: 1400mAh 2) Charge current: 0.75A 3) Max. charge current: 4A 4) Max. discharge current: 30A 5) Cut off voltage: 2.0V 6) Dimension: (D)18.4x (H) 65.2mm 7) weight: 48g (max.)	100	YES
	18650 HD2	3.65V/2000mAh		4.2V	25A	1) Min. capacity: 2000mAh 2) Charge current: 1A (3h) 3) Max. charge current: 4A (50min) 4) Max. discharge current: 25A 5) Cut off voltage: 2.5V 6) Dimension: (D)18.5x (H) 65.2mm 7) weight: 48g (max.)	100	YES
	ICR18650S3	3.6V/2200mAh		4.2V	3.225A	1) Min. capacity: 2150mAh 2) Charge current: 1.075A (3h) 3) Max. charge current: 2.15A (2.5h) 4) Max. discharge current: 3.2A 5) Cut off voltage: 3.5V 6) Dimension: (D)18.5x (H) 65.2mm 7) weight: 45g (max.)	100	YES
	INR18650MF2	3.6V/2200mAh		4.2V	10A	1) Min. capacity: 2100mAh 2) Charge current: 1.050A 3) Max. charge current: 2.15A (2.5h) 4) Max. discharge current: 10A 5) Cut off voltage: 2.75V 6) Dimension: (D)18.4x (H) 65.2mm 7) weight: 44g (max.)	100	YES
	18650 HE2	3.6V/2500mAh		4.2V	20A	1) Min. capacity: 2500mAh 2) Charge current: 1.25A 3) Max. charge current: 4A 4) Max. discharge current: 20A 5) Cut off voltage: 2.5V 6) Dimension: (D)18.5x (H) 65.2mm 7) weight: 48g (max.)	100	YES
	18650 HE4	3.6V/2500mAh		4.2±0.05V	20A	1) Min. capacity: 2500mAh 2) Charge current: 1.25A 3) Max. charge current: 4A 4) Max. discharge current: 20A 5) Cut off voltage: 2.5V 6) Dimension: (D)18.5x (H) 65.2mm 7) weight: 47g (max.)	100	YES
	ICR18650B4	3.6V/2600mAh		4.2V	5A	1) Min. capacity: 2500mAh 2) Charge current: 1.25A 3) Max. charge current: 2.5A 4) Max. discharge current: 5A 5) Cut off voltage: 2.75V 6) Dimension: (D)18.4x (H) 65.5mm 7) weight: 47g (max.)	100	YES
	ICR18650D1	3.75V/3000mAh		4.35V	5.9A	1) Min. capacity: 2900mAh 2) Charge current: 1.45A 3) Max. charge current: 2.9A 4) Max. discharge current: 4.35A 5) Cut off voltage: 3.0V 6) Dimension: (D)18.4x (H) 65.05mm 7) weight: 48.5g (max.)	100	YES
	ICR18650E1	3.75V/3200mAh		4.35±0.05V	4.65A	1) Min. capacity: 3200mAh 2) Charge current: 1.55A 3) Max. charge current: 2.17A 4) Max. discharge current: 4.65A 5) Cut off voltage: 2.75V 6) Dimension: (D)18.4x (H) 65.05mm 7) weight: 49g (max.)	100	YES
	INR18650MH1	3.67V/3200mAh		4.2±0.05V	10A	1) Min. capacity: 3100mAh 2) Charge current: 1.55A 3) Max. charge current: 3.1A 4) Max. discharge current: 10A 5) Cut off voltage: 2.75V 6) Dimension: (D)18.5x (H) 65.15mm 7) weight: 49g (max.)	100	YES
	 INR18650 HG2	3.6V/3000mAh		4.2±0.05V	20A	1) Min. capacity: 3000mAh 2) Charge current: 1.5A 3) Max. charge current: 4A 4) Max. discharge current: 20A 5) Cut off voltage: 2.5V 6) Dimension: (D)18.5x (H) 65.2mm 7) weight: 47g (max.)	100	YES
	 INR18650 MJ1	3.635V/3500mAh		4.2±0.05V	10A	1) Min. capacity: 3400mAh 2) Charge current: 1.7A 3) Max. charge current: 3.4A 4) Max. discharge current: 10A 5) Cut off voltage: 2.5V 6) Dimension: (D)18.5x (H) 65.2mm 7) weight: 49g (max.)	100	YES

VAPPOWER	IMR18350	3.7V/750mAh		4.2V	8A	1) Min. capacity: 750mAh 2) Charge current: 0.375A 3) Max. discharge current: 8A 4) Max. pulse discharge: 15A 5) Cut off voltage: 2.5V 6) Dimemsion: (D)18.2x (H) 35.2mm 7) weight: 20g (max.)	100	YES
	IMR18500	3.7V/1100mAh		4.2V	10A	1) Min. capacity: 1100mAh 2) Charge current: 0.55A 3) Max. discharge current: 10A 4) Max. pulse discharge: 20A 5) Cut off voltage: 2.75V 6) Dimemsion: (D)18.2x (H) 50.2mm 7) weight: 35g (max.)	100	YES
	IMR18650-15	3.7V/1500mAh		4.2V	35A	1) Min. capacity: 1450mAh 2) Charge current: 0.75A 3) Max. discharge current: 35A 4) Max. pulse discharge: 50A 5) Cut off voltage: 2.0V 6) Dimemsion: (D)18.5x (H) 65.0mm 7) weight: 46g (max.)	100	YES
	IMR18650-20	3.7V/2000mAh		4.2V	30A	1) Min. capacity: 2000mAh 2) Charge current: 1A 3) Max. discharge current: 30A 4) Max. pulse discharge: 50A 5) Cut off voltage: 2.5V 6) Dimemsion: (D)18.5x (H) 65.2mm 7) weight: 45g (max.)	100	YES
	IMR18650-25	3.7V/2500mAh		4.2V	35A	1) Min. capacity: 2500mAh 2) Charge current: 1.25A 3) Max. discharge current: 35A 4) Max. pulse discharge: 50A 5) Cut off voltage: 2.5V 6) Dimemsion: (D)18.5x (H) 65.2mm 7) weight: 48g (max.)	100	YES
	IMR18650-30	3.7V/3000mAh		4.2V	30A	1) Min. capacity: 3000mAh 2) Charge current: 1.5A 3) Max. discharge current: 30A 4) Max. pulse discharge: 50A 5) Cut off voltage: 2.5V 6) Dimemsion: (D)18.5x (H) 65.2mm 7) weight: 47g (max.)	100	YES
	IMR18650-32	3.7V/3200mAh		4.2V	10A	1) Min. capacity: 3100mAh 2) Charge current: 1.55A 3) Max. discharge current: 10A 4) Max. pulse discharge: 20A 5) Cut off voltage: 2.5V 6) Dimemsion: (D)18.5x (H) 65.2mm 7) weight: 49g (max.)	100	YES
	IMR18650-35	3.7V/3500mAh		4.2V	10A	1) Min. capacity: 3350mAh 2) Charge current: 1.65A 3) Max. discharge current: 10A 4) Max. pulse discharge: 20A 5) Cut off voltage: 2.5V 6) Dimemsion: (D)18.4x (H) 65.2mm 7) weight: 46g (max.)	100	YES
	IMR26650-42	3.7V/4200mAh		4.2V	40A	1) Min. capacity: 4200mAh 2) Charge current: 2A 3) Max. discharge current: 40A 4) Max. pulse discharge: 60A 5) Cut off voltage: 2.5V 6) Dimemsion: (D)26.5x (H) 68mm 7) weight: 93.5g (max.)	100	YES
	IMR26650-52	3.7V/5200mAh		4.2V	20A	1) Min. capacity: 5200mAh 2) Charge current: 2A 3) Max. discharge current: 20A 4) Max. pulse discharge: 30A 5) Cut off voltage: 2.5V 6) Dimemsion: (D)26.5x (H) 67.5mm 7) weight: 94.5g (max.)	100	YES
	LMP202670	11.1V/950mAh		4.2V	30C	1) Min. capacity: 880mAh 2) Charge current: 900mA 3) Max. discharge current: 27A (30C) 4) Max. pulse discharge: 54A (60C) 5) Cut off voltage: 3.0V 6) Dimemsion: 19.8 x 26 x 70mm 7) weight: 75g (max.)	100	YES
	LMP714021	11.1V/1300mAh		4.2V	20C	1) Min. capacity: 1300mAh 2) Charge current: 1.3A 3) Max. discharge current: 20C 4) Max. pulse discharge: 40C 5) Cut off voltage: 3.0V 6) Dimemsion: 71 x 40 x 21mm 7) weight: 100g (max.)	100	YES